
"EXPRESS MAIL" MAILING LABEL NUMBER

EL 223 803 332 45

DATE OF DEPOSIT: 12-16-01

I HEREBY CERTIFY THAT THIS PAPER OR FEE IS BEING
DEPOSITED WITH THE UNITED STATES POSTAL SERVICE
"EXPRESS MAIL POST OFFICE TO ADDRESSEE" SERVICE
UNDER 37 cfr 1.10 ON THE DATE INDICATED ABOVE AND
IS ADDRESSED TO THE COMMISSIONER OF PATENTS AND
TRADEMARKS, WASHINGTON, D.C. 20231.

MARCIA A. SNOW

TYPED OR PRINTED NAME OF PERSON MAILING

Marcia A. Snow

SIGNATURE OF PERSON MAILING PAPER OR FEE

UNITED STATES PATENT APPLICATION

FOR

BACK-FLOW VALVE AND TRIGGER FOR A CLEANING MACHINE

BEST AVAILABLE COPY

BACK-FLOW VALVE AND TRIGGER FOR A CLEANING MACHINE

BACKGROUND OF THE INVENTION:

This invention relates generally to vacuum type cleaning machines and more particularly concerns back-flow valves and valve triggers facilitating cyclical washing of the cleaning machine filters.

Back flow valves typically employ gates which are directly mechanically or electrically driven. Consequently, the speed of movement of the gate is governed throughout its range of motion. The result is a response time that is detrimental to the smooth operation of the machine, the filtering action being blocked for unnecessarily long intervals because of the slow response of the back-flow valve. Furthermore, these mechanical and electronic systems are extremely complex and expensive and available only on the most expensive cleaning machines. For lower priced equipment, down time for filter replacement or cleaning is required.

In one valve system disclosed in U.S. Patent No. 4,618,352 to Nelson, cams within the system air ducts rotate in direct physical contact with their valve gates, holding the gates in horizontal planes until notches in the cams allow them to rotate into diagonal planes. This system has serious power and efficiency problems. First of all, the cams are disposed on a common shaft. The common shaft arrangement of the cams requires side-by-side alignment of the system ducts transverse to the common shaft. This adds to duct length and imposes location requirements which increase system losses and structural complexity. Second, the notches are angularly displaced on the cams to synchronize the operation of the gates. Since the gates are in direct contact with the cams, the notches must be relatively wide in order for the gates to open for a sufficient interval. This imposes limitations on the blower to vacuum time ratios which greatly reduce the efficiency of the system. Third, in the horizontal condition the gates completely seal the openings to the blower ducts. However, in the diagonal condition only the free ends of the gates engage the vacuum ducts, so that there is no seal and air loss occurs. Fourth,

since the cam notches receive the gates, the cam diameters must be greater than the ducts the gates close. Consequently, for the gates and cams to maintain physical contact, the ducts must be slotted to receive the cams. Therefore, special housings are required to prevent further air losses in the system. Fifth, the cams are constantly driven so that the back-flow cycle occurs throughout the cleaning process, reducing the normal operating efficiency of the system. Sixth, because there is no seal during the vacuum process, the speed of operation of the gate is left essentially to an initial push by the blower and the force of gravity rather than taking advantage of the vacuum to help slam the gate home. Seventh, the blower and the vacuum share a common shaft, so the blower is operating unnecessarily throughout the vacuum process. The composite result of these individual problems is that the system is ineffective for cleaning at any appreciable distance from the machine.

It is, therefore, an object of this invention to provide a back-flow valve and valve trigger which facilitate cyclical washing of the cleaning machine filters. Another object of this invention is to provide a back-flow valve and valve trigger which have a rapid response time so as to limit the duration of the back flow interval. A further object of this invention is to provide a back-flow valve and valve trigger using a gate which is air-flow biased by both a blower and a vacuum source toward a back-flow condition. Yet another object of this invention is to provide a back-flow valve and valve trigger using a gate which is not mechanically controlled during its transition from normal operation to back-flow operation. It is also an object of this invention to provide a back-flow valve and valve trigger using a gate which is not electrically controlled during its transition from normal operation to a back-flow operation. Still another object of this invention is to provide a back-flow valve and valve trigger using a gate which is not governed during its transition from normal operation to back-flow operation. Another object of this invention is to provide a back-flow valve and valve trigger which do not unnecessarily increase the

length of the internal duct system. Another object of this invention is to provide a back-flow valve and valve trigger which eliminate openings and gaps which would cause pressure losses in the system. Still another object of this invention is to provide a back-flow valve and valve trigger in which an external valve trigger controls an internal valve gate. Still another object of this invention is to provide a back-flow valve and valve trigger which provide a relatively short back-flow interval during each filter cycle. Another object of this invention is to provide a back-flow valve and valve trigger which require only intermittent use of the back-flow system during the normal vacuuming process. An additional object of this invention is to provide a back-flow valve and valve trigger which are relatively simple and inexpensive. And it is an object of this invention to provide a back-flow valve and valve trigger which require operation of the blower only during the back-flow process.

SUMMARY OF THE INVENTION:

A valve and a valve trigger are provided which cyclically connect a vacuum and a blower to a filter. The valve has a box with three openings. The first opening is connectable to the vacuum. The second opening is connectable to the blower. The third opening is connectable to the filter. A gate within the box is adapted to be biased by the blower and the vacuum to close the first opening. The gate is held against the bias by the external trigger to close the second opening. The external trigger is intermittently operated and is adapted to intervally release the internal gate to the bias to close the first opening and open the second opening. The preferred gate is a flapper hinged for angular motion between the first and second openings. The preferred trigger is a rotating cam with a follower fixed to the flapper. The cam operation is controlled by a timer. As the cam perimeter remains engaged with the follower, the flapper is held against the bias to close the second opening. An irregularity in the perimeter of the cam intermittently disengages the cam from the follower and releases the flapper to the bias of the air flow, allowing the flapper to slam against and close the first opening and open the second opening. The blower is energized in response to the timer so that it operates only when the cam is rotating.

A plurality of valves can be combined with a single trigger in a system for cyclically connecting a plurality of filters to the vacuum and the blower. In the preferred system, a plurality of cam followers are equally angularly displaced along the perimeter of a circular cam. The cam irregularity is shaped to release each gate for approximately 1/12 rotation of the cam and intervally releases the gates to the bias to sequentially close their first openings.

BRIEF DESCRIPTION OF THE DRAWINGS:

Other objects and advantages of the invention will become apparent upon reading the following detailed description and upon reference to the drawings in which:

5 Figure 1 is a mechanical schematic drawing of a three filter cleaning machine employing three back-flow valves and a single valve trigger;

 Figure 2 is a perspective assembly view of the back-flow valves and valve trigger of Figure 1;

10 Figure 3 is a perspective view of the assembled back-flow valve and valve trigger of Figure 1;

 Figure 4 is a perspective assembly view of a preferred embodiment of the valves of Figure 1;

 Figure 5 is a top perspective view of the assembled valve of Figure 4;

15 Figure 6 is a bottom perspective view of the assembled valve of Figure 4;
and

 Figure 7 is an electrical schematic drawing of the machine of Figure 1.

20 While the invention will be described in connection with a preferred embodiment, it will be understood that it is not intended to limit the invention to that embodiment. On the contrary, it is intended to cover all alternatives, modifications and equivalents as may be included within the spirit and scope of the invention as defined by the appended claims.

DETAILED DESCRIPTION:

Turning first to Figure 1, a three-filter cleaning machine employing three back-flow valves and a single valve trigger is illustrated. During normal operation, a vacuum source S connected through valve V1, V2 or V3 pulls air contaminated with undesirable particles into three filters F1, F2 and F3 which remove the undesirable particles. While most of the accumulated particles are discharged into a filter pan, some of the particles amass on and clog the filter walls, diminishing the efficiency of the system. For back-flow operation, a blower B is connected to push air through the valves V1, V2 and V3 to their respective filters F1, F2 and F3 to dislodge the clogging particles from the filter walls. Each of the valves V1, V2 and V3 has a gate G1, G2 and G3, respectively, which seals off flow from the blower B into the valves V1, V2 or V3 and permits the vacuum source S to draw contaminated air into the filters F1, F2 and F3 during the normal vacuuming process. The gates G1 and G2 and G3 are mechanically held in place against the bias created by the blower B and the vacuum source S during the normal vacuuming process by a trigger T. The trigger T cyclically sequentially releases the gates G1, G2 and G3 to the bias of the blower B and the vacuum source S to cause them to seal off the suction of the vacuum source S and allow air pushed by the blower B to blast into the filters F1, F2 and F3. The trigger T is external to the valves V1, V2 and V3. In switching to the back-flow process, the trigger T completely disengages mechanical connection to the gates G1, G2 and G3 so that the bias afforded by the blower B and vacuum source S causes the gates G1, G2 and G3 to rapidly slam from the vacuum to the back-flow condition.

Looking now at Figures 2 and 3, the valve deck 10 is illustrated in greater detail. Valves V1, V2 and V3 are mounted on a base 11. For the three-filter machine illustrated, the base 11 has three passages 12, 13 and 14 which are equidistantly spaced from a center point 15 on axes 16, 17 and 18 and are equally angularly displaced from each other. The filters F1, F2 and F3 are mounted below

the plate 11 and aligned with the passages 12, 13 and 14, respectively, as best seen in Figure 1. The valves V1, V2 and V3 are secured to the top face of the base 11 by mounting plates 21 which receive bolts 22 extending upwardly from the base 11.

5 The valves V1, V2 and V3 are illustrated in greater detail in Figures 4-6. The mounting plates 21 have openings 23 which align with the passages 12, 13 and 14 through the base 11. A hub 24 at the center of each opening 23 allows the filter F1, F2 or F3 to be engaged beneath its respective opening 23. Each of the valves V1, V2 and V3 has sidewalls 25, 26, 27 and 28 and a cover 29 which, in cooperation with the mounting plate 21, defines the valve box. Two of the walls 25 and 28 have ports 31 and 32. Adapters 33 and 34, respectively, are secured at the ports 31 and 32 to facilitate connection of system ducts, seen in Figure 1, to the valve box. As shown, the ports 31 and 32 are in adjacent orthogonal sidewalls 25 and 28. A clapper 35, such as an approximately square sheet of metal stock, has circular disks 36 and 37 of compressible material attached to its opposite faces. The adapters 33 and 34 have circumferences within the valve boxes to provide a suitable sealing surface and the disks 36 and 37 are sized and textured to cooperate with the adapters 33 and 34 to seal the passages 31 and 32. One edge of the clapper 35 abuts and is fixed to a shaft 38 which extends above and below the upper and lower edges of the clapper 35. A brass bushing 42 is fitted into an aperture 41 in the corner of the cover 29 at the junction point of the sidewalls 25 and 28. Another brass bushing 44 is fitted into another aperture 43 in the mounting plate 21 which is vertically aligned with the aperture 41 in the cover 29. The upper and lower ends of the flapper shaft 38 are journaled for rotation in the bushings 42 and 44 so that the flapper 35 can rotate between a first position in which one of the disks 36 seals one of the ports 31 and a second position in which the other of the disks 37 seals the other of the ports 32. The upper end 45 of the shaft 38 further extends through its bushing 42 upwardly beyond the top of the cover 29 for

engagement with one end of a follower arm 46. The arm 46 is secured proximate one of its ends to the top end of the shaft 45. A threaded screw 47 through a split in the arm 46 tightens the aperture 48 into which the end 45 of the shaft is inserted. The arm 46 extends radially outwardly from the shaft 38 to a cam follower 51 which is journaled for rotation using a washer 52 on a post 53 extending upwardly from the arm 46. The seams of the valve box are sealed with a suitable duct sealant to insure the pneumatic integrity of the valves V1, V2 and V3.

Returning to Figures 2 and 3, a motor 54 is mounted beneath a motor mounting plate 55 with the shaft 56 of the motor 54 extending upwardly through the mounting plate 56. The bottom face of the motor mounting plate 56 is fastened to the top faces of the valve covers 29 with the axis 57 of the motor shaft 56 in vertical alignment through the center point 15 of the symmetrical arrangement of valves V1, V2 and V3. A circular cam 58 is concentrically mounted on the top of the motor shaft 56 by the cam hub 59. The diameter of the cam 58 is such that its circumference engages the cam followers 51 to hold the flapper disks 36 against the valve ports 31. This can be assured by adjustment of the angular position of the follower arms 46 in the gate shafts 38. An irregularity 61 in the circumference of the cam 58 completely disengages the cam 58 from mechanical contact with the follower 51 so that, when the follower 51 is released, its corresponding flapper 35 is free to rotate on its shaft 38 until the other disk 37 on the flapper 35 seals the other port 32 of its respective valve V1, V2 or V3. Looking at Figures 1, 2 and 3, a manifold 62 has outlets 63 connected by ducts 64 to their respective inlet ports 33 in the valves V1, V2 and V3. The blower B is connected by a duct 65 to the inlet of the manifold 62. Similarly, the vacuum source S is connected to the ports 32 of the valves V1, V2 and V3 by ducts 66.

Looking at Figures 1 and 7, the operation of the machine can be understood. The cam drive motor 54 is controlled through a switch 67 and time delay circuit 68 which are part of the trigger T. The cam 58 is normally engaged with the cam

followers 51 so as to hold the flappers 35 with their disks 36 sealing the blower inlet ports 31 into the valves V1, V2 and V3. In this position, the suction of the vacuum source S and the pressure from the blower B, the former drawing against the vacuum side disks 37 and the latter pushing against the blower side disks 36, biases the flappers 35 to rotate from the blower inlet ports 31 toward the vacuum outlet ports 32. However, the flappers 35 are held against the bias by the mechanical engagement of the cam 58 with the followers 51. As the cam motor 54 rotates the cam 58, the irregularity 61 in the cam circumference sequentially releases the cam followers 51 completely from mechanical engagement so that the gates G1, G2 and G3 are free to rotate in response to the bias to open the blower inlet ports 31 and slam the vacuum outlet ports 32 closed. Thus, air is no longer drawn by the vacuum source S into the filter F1, F2 or F3 associated with the released gate G1, G2 or G3 in the forward flow direction 71 but air is blown into the filter F1, F2 or F3 in reverse-flow direction 72 to dislodge particles collected on the filter walls during the vacuuming process. The contour of the irregularity 61 of the cam 58 is selected so as to release each cam follower 51 from mechanical engagement for approximately 1/12 of a rotation of the cam 58. Because of the rapid response of the mechanically released gates G1, G2 and G3, each filter F1, F2 and F3 experiences back flow for only 1/12 of a cam rotation and the entire system is experiencing back flow for only 1/4 of a cam rotation. Thus, even during the back flow process, the normal vacuum process continues at 100% effectiveness for 3/4 of the cam rotation. Furthermore, the timer rheostat 68A can be adjusted by the machine operator to cause its switch 68A to operate at any desired interval, preferably in a range of from 1.5 to 30 minutes. When the switch 67 is closed, a first relay 81 is energized, closing its normally open contacts 81A to energize the vacuum source S. The timer 68 is energized simultaneously through normally closed contacts 84A. As long as the timer 68 is energized, it will cause its switch 68B to operate at the intervals set by the timer rheostat 68A. Assuming, for

example, a selected interval of twenty minutes, the timer switch 6B will close twenty minutes after the switch 67 is turned "ON" and every twenty minutes thereafter. This will energize a second relay 83 which closes two of its normally open contacts 83A and 83B to engage the blower B and the cam motor 54, respectively, and third normally open contacts 83C in the circuit of a third relay 84. The third relay 84 controls the normally closed contacts 84A which control the timer 68. The energized cam motor 54 causes the cam 58 to rotate. A post 85A fixed to and rotating with the cam 58 activates a proximity switch 85 in the circuit of the third relay 84. The proximity switch is normally open. If the blower B and cam motor 54 are energized, the second relay contacts 83C are closed. When the proximity switch 85 closes, the third relay 84 opens the contacts 84A to de-energize the timer 68, opening the timer switch 68B and de-energizing the second relay 83 to shut off the blower B and cam motor 54 and reset the system which will repeat itself when the selected time interval of twenty minutes has elapsed. The proximity switch 85 is operated after one revolution of the cam 58. Therefore, each of the filters F1, F2 and F3 will receive one blast of blower air every twenty minutes and the blower B and cam motor 54 are energized for only one rotation of the cam 58 every twenty minutes. If, for example, the cam motor 64 drives the cam 58 at one (1) rpm, the back-flow process is in operation for only 1/20 of the vacuuming process and each filter will sequentially receive one five second blast of blower air during the one minute back-flow interval. In this manner, the back-flow process can be used to eliminate down time to replace or clean filters without any significant reduction in the power and efficiency of the vacuum process, even while back-flow is occurring. While the invention has been described in relation to a three-valve system, any number of valves and filters can be used applying the principles of the invention.

Thus, it is apparent that there has been provided, in accordance with the invention, a back flow valve and valve trigger for a cleaning machine that fully satisfies the objects, aims and advantages set forth above. While the invention has

been described in conjunction with a specific embodiment thereof, it is evident that many alternatives, modifications and variations will be apparent to those skilled in the art and in light of the foregoing description. Accordingly, it is intended to embrace all such alternatives, modifications and variations as fall within the spirit of the appended claims.

5

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000